

20Mt IMO1 Bitutainer™ Model TRT-T-878



Suitable for Storage and Transportation of Hot Liquid Bitumen, Bitumen Emulsions, Light and Heavy Fuel Oils

Fully IMDG Compliant with ADR/RID, US DOT/TC

- Nominal Capacity 21,000 Litres
- Transported as a Standard 20 ft ISO Tank Container
- ISO 1496 Part 3 - Type 75 - "Tank Containers"
- UN Coded T3 (IMO1) Lloyd's Approval
- Ideal for Sea, Road and Rail Transportation
- Design Allows Partial Payloads to be Carried (Baffled)
- Unique High Performance Heating Systems (8-10 Deg./Hr.) through Twin Heating Tubes
- High Value Factory Installed Insulation with Robust Outer Skin
- Fully Framed with Corner Twist Locks which have Damage Reinforcement Plates



Accessories and Auxilary Optional Items:

- Quick Fit Diesel Burners
- Stainless Steel Flameliners
- Pump & Flexible Hose Sets

Ratings:

Max GW	26,000 Kgs
Payload	20,100 Kgs
Tare Wt.	< 5,900 kgs

Measures:

Length	6058 mm (20')
Width	2438 mm (8')
Height	2591 mm (8'6")