

24Mt IMO1 Bitutainer™ Model TRT-T-778 For Direct Fire Heating



Suitable for Storage and Transportation of Hot Liquid Bitumen, Bitumen Emulsions, Light and Heavy Fuel Oils.

Fully IMDG Compliant with ADR/RID, US DOT/TC

- Nominal Capacity 24,000 Litres
- Transported as a Standard 20 ft ISO Tank Container
- ISO 1496 Part 3 - Type 75 - "Tank Containers"
- UN Coded T3 (IMO1) with Lloyd's Approval
- Ideal for Sea, Road and Rail Transportation
- Design Allows Partial Payloads to be Carried (Baffled)
- Vessel Pressure Tested to 4 bar with Pressed Corten Steel Exterior Panels
- High Quality Construction, Fully Insulated with a Robust Outer Skin
- Can be Stacked 6 High
- Fully Framed with Corner Twist Locks which have Damage Re-Enforcement Plates
- Unique High Performance Heating Systems (8-10 Deg./Hr Through Heating Tubes)



Ratings:

Max GW	30,000 Kgs
Payload	24,000 Kgs
Tare Wt.	< 6,000 Kgs

Measures:

Length	6058 mm (20')
Width	2438 mm (8')
Height	2591 mm (8'6")