

## 24Mt IMO1 Bitutainer™ Model TRT-T-678



*Suitable for Storage and Transportation of Hot Liquid Bitumen, Bitumen Emulsions, Light and Heavy Fuel Oils*

**Fully IMDG Compliant with ADR/RID, US DOT/TC**

- Water Capacity 24,000 Litres
- Transported as a Standard 20 ft ISO Tank Container
- ISO 1496 Part 3 - Type 75 - "Tank Containers"
- UN Coded T3 (IMO1) with Lloyd's Approval
- Ideal for Sea, Road and Rail Transportation
- Unique Design Allows Partial Payloads to be Carried (Baffled)
- High Performance Heating Systems (8-10 Deg. / Hr) Through Twin Heating Tubes
- High Value Factory Installed Insulation with Robust Outer Skin
- Outright Purchase - Lease Purchase & Rental Options Available



### Accessories and Auxiliary Items:

- Quick Fit Diesel / Electric Burners
- Stainless Steel Flame Liners
- Pump & Flexible Hose Sets

### Ratings:

Max GW            30,000 Kgs  
 Payload           24,000 Kgs  
 Tare Wt.           < 6,000 Kgs

### Measures:

Length            6058 mm (20')  
 Width             2438 mm (8')  
 Height            2591 mm (8'6")