

40ft Storage Bitutainer™  
 Model TR-T-103  
 (For Thermal Oil or Steam Heating)



Suitable for Storage of Hot Liquid Bitumen,  
 Bitumen Emulsions, PMBs and Heavy Fuel Oils

**Provides an Innovative and Versatile Concept in Temporary Bitumen Storage**

- Nominal Capacity 65,000 Litres
- ISO 1496 Part 3 - Type 70 Classification
- Factory fitted double layered thermal oil heating coil
- Recirculation connection options available
- High Value Factory Installed Insulation and Pressed Corten Steel Outer Skin
- Fully Framed with Corner Twist Locks and Damage Reinforcement Plates
- Transported as a Standard 40 ft ISO Tank Container with Lloyds Approval
- Range of bitumen handling equipment available including pumps and hoses
- **Ideal for use as Individual Static Storage Tanks or as a part of an interconnected Storage Facility System**



**Heating equipment required for unit:**

- Simple connection to an existing Thermal Oil Heating Circuit on site
- Valves suitable for Thermal Oil and Steam available upon request

**Ratings:**

Max GW 75,000 Kgs  
 Payload 65,000 Kgs  
 Tare Wt. <10,000 Kgs

**Measures:**

Length 12,192 mm (40')  
 Width 2,438 mm (8')  
 Height 2,896 mm (9'6")